

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 10-304658

(43)Date of publication of application : 13.11.1998

(51)Int.Cl.

H02M 3/28

(21)Application number : 09-107186

(71)Applicant : YOKOGAWA ELECTRIC CORP

(22)Date of filing : 24.04.1997


(72)Inventor : HANAWAKA MASUO
OTA MASANORI
NISHIYAMA TOMOHIRO

(54) SWITCHING POWER SUPPLY

(57)Abstract:

PROBLEM TO BE SOLVED: To provide a switching power supply of a small power loss by stabilizing the output voltage at a light load without using a dummy resistor.

SOLUTION: This power supply device is provided with a main switch for turning the DC current applied to a primary winding N_p on and off, a secondary-side rectifying and smoothing circuit for rectifying and smoothing an on/off signal induced in a secondary winding N_s and then supplying the rectified and smoothed signal as a main output voltage V_o , an auxiliary power supply section for rectifying and smoothing an on/off signal induced in a bias winding N_b and then supplying the rectified and smoothed signal as an auxiliary supply voltage V_{cc} , an error amplifier which generates an error voltage signal between the auxiliary supply voltage output from the auxiliary power supply section and a reference voltage, and a comparator 23 which sends an on/off control signal to the main switch in such a direction as to lower the error voltage signal sent out from the error amplifier. This power supply device is also provided with a light load switch controlling section 30, which temporarily stops the on/off operation of the main switch when the main output voltage V_o rises above the upper limit voltage and restarts the on/off operation of the main switch, when the main output voltage V_o drops below the lower limit voltage.



LEGAL STATUS

[Date of request for examination] 15.07.1997

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number] 3206488

[Date of registration] 06.07.2001

[Number of appeal against examiner's decision
of rejection]

[Date of requesting appeal against examiner's
decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office